


# VEST iMX8M Mini Dev Kit H

VEST is a leading embedded solutions provider, committing to excellence and innovation. Our Development Kit expedite product development, enabling swift market entry for your products and ensuring a competitive advantage.



Industrial /  
Commercial  
IoT



Efficient  
CPU



Robust Security  
Features



Edge  
Computing

## ABOUT OUR PRODUCT

Introducing the VEST i.MX8M Mini Development (Dev) Kit with Hailo-8R™. This compact solution is a Single Board Computer (SBC) that enable designers to deliver an intuitive, highly interactive, and immersive user experience. The Development Kit comes with choice of 7" or 10.1" LCD panel.

Unleash the full potential of the NXP i.MX8M Mini, featuring an advanced implementation of a Quad Arm® Cortex®-A53 core, which operates at a top clock speed of 1.8 GHz. This provides rich multimedia functionality for general purpose Human-Machine-Interface (HMI) solutions enabling touch, voice, graphics, video.

Further upgrade to include AI / ML capabilities via integration of Hailo-8R™ AI accelerator. VEST software board support package contains drivers for Hailo-8R™ AI accelerator (up to 13 TOPS capacity).

This Dev Kit is versatile and suitable for diverse range of applications, such as

- Edge Computing
- Video / Audio Conferencing
- Advanced Human Machine Interface Application
- Point of Sales, Digital Signage, Smart Retail, Smart Cities
- Point of Care
- Portable Test and Measurement Instruments
- Automation for Industry 4.0

## Key Features

- Rich multimedia capabilities for advanced HMI application
- A general-purpose Cortex®-M4 400 MHz core processor is for low-power processing
- Built-in 10W audio amplifier (plug and play speaker driver)
- Secured data integrity, safeguard against unauthorized access
- Multiple high-speed interfaces that comply with industrial standards facilitate seamless integration with various peripherals
- Integrated Hailo-8R™ AI accelerator with 13 TOPS AI computing budget

## Support



**VESTConnect360**  
Cloud Management System

**HAILO**  
Empowering Intelligence

### ADVANCED PRODUCTS CORPORATION PTE LTD (APC)

All product specifications are subject to change without notice. Last updated: March-2024.  
Copyright © 2024 APC Pte Ltd. All rights reserved. No part of this document may be photocopied, reproduced, or translated to another language without the prior written permission of APC Pte Ltd. All trademarks, logos and brand names used in this brochure are the property of their respective owners. Their use does not constitute an endorsement or affiliation with APC Pte Ltd.



**Scan here  
to purchase**

Website: [apc-vest.com](http://apc-vest.com)

Email: [sales@apc-vest.com](mailto:sales@apc-vest.com)

E-Store: [shop.apc-vest.com](http://shop.apc-vest.com)

LinkedIn: [www.linkedin.com/company/advanced-product-corporation](http://www.linkedin.com/company/advanced-product-corporation)

## Specifications (VEST iMX8M Mini Dev Kit H)

CPU Details	
CPU	i.MX8M Mini   4x Cortex®-A53 @ 1.8GHz, Cortex®-M4 @ 400MHz
GPU	GCNanoUltra for 3D Graphics   GC320 for 2D
AI Accelerator	Hailo AI Accelerator module, Hailo-8R up to 13 TOPS
Memory	
Memory	2GB 32-bit LPDDR4-3000
Storage	8GB eMMC5.1
External Storage	Micro SD 3.0 Socket push-push type
Operating System	
BSP	Yocto Linux, Ubuntu and Android
Multimedia	
Video Encoder	1080p60, H.264, VP8
Video Decoder	1080p60, H.265, H.264, VP9, VP8
Camera	1x MIPI CSI
Display Controller	Support up to 1080p60 display through MIPI DSI
Display and Touch	On board LVDS and I2C Touch Connector for 7" or 10" LCD Panel   Socket   Dual Channel 4-lane LVDS   4-lane MIPI-DSI   I2C Touch   PWM   Up to 1A Backlight Output
Audio and Video	Microphone Input (2mm pitch 2 pin header)   2mm pitch, 4 pin header for Speaker L&R, Up to 10W/ch into 8ohm load   Compatible to NXP MIPI-HDMI adapter card
Connectivity	
Wireless	On Board Dual Band Wi-Fi / Bluetooth Module (Optional)
USB	USB 2.0 OTG Mirco, Type B   6x USB 2.0 Host, Type A
Serial Communication	RS485 (default) or RS232   CAN-1x 2mm pitch 3 pin header
Ethernet	1x Gigabit Ethernet with AVB, IEEE 1588, EEE (Energy Efficient for Low Power)
I/O Expansion	0.5mm pitch, 2 x 25 pin header for 4-lane MIPI CSI   SPDIF   SPI   PWM   UART   I2C   GPIO   Half & Full Size Mini PCIe with Mirco SIM Card Socket used by Hailo 8R
Debugging & Programming	Debug-2x UART Header, 2.54mm pitch 6 pin header   JTAG-1.27 mm pitch 2x 5 pin header
Buttons and Indicators	1x On/Off Button   1x Reset Button   1x 2mm pitch 3 pin header for Reset & Power   1x GPIO Controlled LED Indicator
Power	12-24VDC, 2 pin 4.2 mm pitch Mini Fit JR Header
Panel	
LCD Panel Size	7" LCD Panel, 10" LCD Panel (Optional)
Physical	
Form Factor	147mm x 89mm
Operating Temperature	Commercial   Industrial (Optional)
Ordering Information	
Part No.	VES-8MM-07-H8R-SBC-DEV

